



Cyclone Air 22

Mineral oil-based ash free Airline Lubricant

Product code: C044

Product Description:

Cyclone air is a premium quality, low viscosity airline oil, specifically designed for the lubrication of air tools. It has a low pour point and special additives to protect against rust, corrosion, and water washing. This grade also has excellent anti-wear and EP properties, providing component protection in the most demanding of systems.

Benefits:

- Excellent oxidation stability
- Low evaporation and carry over
- Excellent anti-wear and EP properties
- Excellent Resistance to oxidation and thermal degradation
- Superior mist-forming properties
- Excellent demulsibility characteristics
- Low Carbon and deposit forming tendency

Application:

Recommended for air tools of all types including road drills, jack hammers, air speed saws and torque wrenches. Also recommended for air motors and the lubrication of pneumatic rams and cylinders. Can also be used for general lubrication in industrial applications.

Typical Test Data:

Cyclone	Air 22
Product Code	C044
ISO VG	22
Appearance	Straw
Specific Gravity @ 15.6°C	0.874
Kin. Viscosity @ 40°C (cSt)	22.1
Kin. Viscosity @ 100°C (cSt)	5.38
Viscosity Index	99
Pour Point (°C)	-12
Flash Point (°C)	197

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all our customers.