



EXCELLENCE IN LUBRICANTS

TECHNICAL DATA SHEET

Excelcut 444V



EXOL LUBRICANTS LIMITED

ALL SAINTS ROAD, WEDNESBURY, WEST MIDLANDS, ENGLAND, WS10 9LL

TEL: +44 (0) 121 568 6800 • FAX: +44 (0) 121 568 6720

WWW.EXOL-LUBRICANTS.COM



Excelcut 444V

Evaporative metal forming lubricant

Product code: N189

Product Description:

Excelcut 444V is a very low viscosity metalworking lubricant based on low odour, light hydrotreated petroleum distillates and fortified with synthetic high lubricity additives. It is designed to lubricate light to medium duty metal forming operations and then evaporate to leave no residual film.

Benefits:

- Low odour
- Excellent lubricity
- Multi metal compatibility
- Eliminates the need to degrease

Applications:

Excelcut 444V is suitable for use on a range of metalworking applications such as pressworking, stamping and fine blanking on both ferrous and non-ferrous materials.

Typical Test Data:

Appearance	Pale/colourless liquid
Specific Gravity @ 15.6°C	0.808
Kinematic Viscosity @ 40°C (cSt)	1.80
Flash Point PMCC (°C)	>70
Copper Corrosion, 3hrs @ 100°C	Class 1

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.